

US005462529A

United States Patent [19]

Simpson et al.

[11] Patent Number:

5,462,529

[45] Date of Patent:

Oct. 31, 1995

[54]	ADJUSTABLE TREATMENT CH	AMBER
	CATHETER	

[75] Inventors: John B. Simpson, Woodside; Scott C.

Anderson, Mountain View, both of

Calif.

[73] Assignce: Technology Development Center,

Redwood City, Calif.

[21] Appl. No.: 128,948

[22] Filed: Sep. 29, 1993

[51] Int. Cl.⁶ A61M 25/00

[52] **U.S. Cl.** **604/101**; 604/96; 604/164

604/96, 19, 22, 27, 43, 35, 49; 606/192,

194, 167, 170, 180

[56] References Cited

U.S. PATENT DOCUMENTS

550,238	11/1895	Allen, Jr
4,573,966	3/1986	Weikl et al
4,655,746	4/1987	Daniels et al
4,771,777	9/1988	Horzewski et al.
4,832,028	5/1989	Patel .
4,883,459	11/1989	Calderon .
4,911,163	3/1990	Fina.

5,059,178 10/1991 Ya .
5,090,960 2/1992 Don Michael .
5,102,390 4/1992 Wright .
5,176,693 1/1993 Wright .
5,181,920 1/1993 Mueller et al .
5,281,200 1/1994 Corso, Jr. et al .
5,318,576 6/1994 Plassche, Jr. et al .

Primary Examiner—C. Fred Rosenbaum Assistant Examiner—Perry E. Van Over Attorney, Agent, or Firm—Douglas A. Chaikin

57] ABSTRACT

Disclosed herein is a catheter device for treatment of disease in biological conduits. The device has inner and outer coaxial catheter members, each having an inflatable balloon attached near its distal end. When the balloons are inflated, a sealed treatment chamber is created between the balloons. The length of the treatment chamber is adjustable by sliding the coaxial catheter members with respect to each other to obtain a desired separation between the attached balloons before inflation. Biological debris is trapped within the chamber and removed by infusion and aspiration of a flushing fluid, reducing the risk of myocardial infarction. Adjunctive treatment devices can be inserted into the sealed treatment chamber through a lumen of the outer coaxial member.

21 Claims, 3 Drawing Sheets

